

TOROTEC 0W-30 PSA

Product Code: PCM043 | **Revision:** 20240123



Fully synthetic, ACEA C2 automotive engine oil for PSA Group vehicles.

Available Pack Sizes

1L

5L

20L

60L

205L

1000L



Applications

A fully synthetic and mid SAPS engine oil formulated for use with modern petrol and diesel engines, particularly Citroën, DS and Peugeot vehicles. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle.

Recommended by Aztec Oils as suitable for the following applications

ACEA C2
PSA B71 2312

Benefits

- Compatible with diesel particulate filters (DPF) and three-way catalysts (TWC).
- Enhanced low temperature performance.
- Excellent engine cleanliness.
- Offers extended service intervals.
- Optimised fuel efficiency.
- Superior performance under both high and low temperature conditions.
- Supreme levels of engine protection.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.844
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	54
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	9.7
Total Base Number (mg KOH/g)	ASTM D2896	6.1
Viscosity Index	ASTM D2207	167

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.