

TOROTEC 5W-30 MP

Product Code: PCM044 | **Revision:** 20240819



Fully synthetic automotive engine oil, ACEA A3/B4

Available Pack Sizes



Applications

A fully synthetic engine oil for use with petrol and diesel engines. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability, ensuring optimum performance and delivering outstanding durability in all conditions for the most demanding motorist. Excellent low temperature properties ensure the oil circulates rapidly, improving cold starting and provides excellent lubricity to reduce internal friction during operation.

Recommended by Aztec Oils as suitable for the following applications

ACEA A3/B4
API SL/CF
GM/Opel GM-LL-A-025, GM-LL-B-025
Mercedes-Benz 226.5, 229.3, 229.5
Renault RN0700/0710
VW 502.00/505.00

Benefits

- Ensures lubricant performance over extended drain intervals.
- Excellent start-up protection.
- Improved efficiency over traditional engine oils.
- Long term anti-wear and oxidation stability.
- Maintains very high standards of engine cleanliness.
- Superior performance at high temperature and low temperature conditions.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.846
Flash Point (°C)	ASTM D92	220
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	72
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	12
Pour Point (°C)	ASTM D97	-40
Total Base Number (mg KOH/g)	ASTM D2896	10.2
Viscosity Index	ASTM D2207	165

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.