





# **TOROTEC 0W-20 LONGLIFE**

**Product Code:** PCM046 | **Revision:** 20220907



Fully synthetic, low viscosity automotive engine oil for VW vehicles.

### **Available Pack Sizes**











### **Applications**

The latest generation fully synthetic and mid SAPS engine oil formulated for use with modern petrol and diesel engines, particularly vehicles in the VW Group. Utilising a combination of a unique additive technology and our specialist Adaptive Molecular Technology to maintain engine power, maximum efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle in mixed driving conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA C5 Porsche C20 VW 508.00/509.00

### **Benefits**


- Advanced anti-wear technology helps to protect engine components.
- Compatible with diesel particulate filters (DPF) and three-way catalysts (TWC), including those utilising SCR technology.
- Contains a chemical marker as specifically required by VW.
- Excellent low temperature performance.
- Exceptional fuel economy.
- High performance with outstanding wear protection.
- Maintains very high standards of engine cleanliness.

1000L	
	<u> </u>

Typical Test Data			
Appearance		Clear & bright	
Colour		Green/blue	
Density @ 15°C (kg/m3)	ASTM D4052	0.849	
Flash Point (°C)	ASTM D92	>200	
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	44	
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	8.3	
Pour Point (°C)	ASTM D97	-45	
Total Base Number (mg KOH/g)	ASTM D2896	>6.0	
Viscosity Index	ASTM D2207	167	

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.







## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- When disposing of the product after use, please protect the environment and comply with local regulations.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.