

## TOROTEC 5W-30 TSL

**Product Code:** PCM048 | **Revision:** 20240112



Fully synthetic & mid SAPS automotive engine oil, ACEA C2/C3.

### Available Pack Sizes



### Applications

A fully synthetic and mid SAPS engine oil formulated for use with petrol and diesel engines requiring ACEA C2 or C3. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability whilst ensuring optimum performance and supporting exhaust after-treatment devices throughout the vehicle's lifecycle in a multitude of driving conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA C2, C3  
API SN/CF  
GM dexos2™  
Mercedes-Benz 229.51, 229.52

### Benefits

- Covers a wide range of vehicles requiring ACEA C2 or C3.
- Excellent high and low temperature performance.
- High standards of engine cleanliness.
- Increased fuel efficiency.
- Long term anti-wear and oxidation stability.
- Maintains performance over extended service intervals.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	75
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	12.0
Pour Point (°C)	ASTM D97	-40
Viscosity Index	ASTM D2207	156
Total Base Number (mg KOH/g)	ASTM D2896	7.6

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.