

METALTEC MIRACOR SCAFFTECH

Product Code: RUS014 | **Revision:** 20250616



A rust protection oil used to protect and lubricate scaffolding pipes.

Available Pack Sizes

20L

205L

Applications

A rust protection oil used in the building and construction industry. Provides a rust preventative film which repels water and stops corrosion, also helps loosen screws, bolts and nuts, it also dries quickly after application saving time and labour.

Suitability

Can be applied by brushing or spraying but its dewatering action is most effective if the articles to be protected can be immersed in a dip tank.
Designed for application to scaffolding equipment to help remove rust and prevent future corrosion.
Easily removable with good quality solvent or alkali cleaners.
Suitable for application to mild steel, pressed parts, sheet metal parts etc.

Benefits

- Excellent maintenance product.
- Leaves protective film on applied surfaces.
- Loosens binding screws, nuts, etc.
- Penetrates and cleans intricate shapes.
- Prevents rusting by displacing water.
- Quick drying.

Typical Test Data

Appearance		Liquid
Colour		Blue
Density @ 15°C (kg/m ³)	ASTM D4052	0.8
Odour		Mild
Freezing Point (°C)		-5
Flash Point (°C)	ASTM D92	>75
Solids Content (%)		30

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



AZTEC OILS

THE LUBRICATION SPECIALISTS



Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.