

## METALTEC MIRACOR 625

**Product Code:** RUS018 | **Revision:** 20240820



A solvent deposited short-to-medium term rust preventative.

### Available Pack Sizes



### Applications

An oil-based rust preventative carefully formulated using solvent refined paraffinic base oil of naturally low aromaticity. It leaves a non-drying light oily film containing inhibitors and surface-active agents, which does not harden with age.

### Suitability

Can be applied by brushing or spraying but its dewatering action is most effective if the articles to be protected can be immersed in a dip tank. Easily removable with good quality solvent or alkali cleaners.

Ideal for the temporary protection of finished components and machinery internals such as engines, gearboxes and hydraulic components. Has been found highly effective in the protection of sheet metal.

### Benefits

- Effective corrosion protection.
- Oily film does not harden with age.
- Very versatile and can be used for a range of applications.

### Typical Test Data

Appearance		Straw/light brown liquid
Drying Time (hours)		0
Film Type		Oil
Film Thickness (µm)		4
Indoor Protection (months)		6
Outdoor Protection (months)		3
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	26
Flash Point (°C)	ASTM D92	>180
Solids Content (%)		100
Solubility		Negligible in water, soluble in oil

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.