

METALTEC MIRACOR 630 PL

Product Code: RUS030 | **Revision:** 20240820



A medium term rust preventative with pressing and molding performance.

Available Pack Sizes



Applications

An oil-based, barium free rust preventative sheet coating oil with the additional lubricity to provide pressing and molding performance. Many forming operations can be carried out without the need for additional lubricants. This makes the product of value in the automotive industry where a single product is needed to provide corrosion protection, lubricate in a forming operation and then be easily removed without interfering with any of the further operations.

Suitability

20 - 40°C is the recommended application temperature and increasing the temperature will aid in the filtration of the product.
Can be applied by brushing, rolling, spraying although its dewatering action is most effective if the articles to be protected can be immersed in a dip tank.
Easily removable with good quality solvent or alkali cleaners.

Benefits

- Barium free.
- Compatible with the bodywork process common in automotive manufacture.
- Effective corrosion protection.
- Improved forming performance without the need for further lubricants.

Typical Test Data

Appearance		Undyed, amber liquid
Film Type		Oil
Film Thickness		2g/m ²
Indoor Protection (months)		18
Outdoor Protection (months)		6
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	30
Solubility		Negligible in water, soluble in oil
Flash Point (°C)	ASTM D92	>140

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.



AZTEC OILS

THE LUBRICATION SPECIALISTS



Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.