


MANUTEC SLIDEWAY M 46

Product Code: SLI012 | **Revision:** 20250227



Premium anti-fling slideway lubricant.

Available Pack Sizes



Applications

Premium slideway lubricants manufactured from high viscosity index solvent refined base oils, they contain tackiness and lubricity additives to prevent stick-slip of machine tool slides or been washed away by cutting fluids.

Benefits

- Advanced EP & tackiness properties.
- Protects metals against staining and corrosion.
- Excellent stick-slip performance.
- Outstanding resistance to oxidation, corrosion and wear.
- Superb demulsification properties to readily separate from water

Typical Test Data

Density @ 15°C (kg/m3)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	46
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	6.7
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	97

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.