

## COMPOUNDED BEARING OIL 460C

**Product Code:** STO004 | **Revision:** 20250627



LBO460C

### Available Pack Sizes



### Applications

A blend of solvent refined mineral oil and compounding esters for enhanced lubricity. As well as increasing the lubricity ability of the oil, the fatty compounding additive also enables the lubricant to function in the tracing of moisture by promoting emulsification whilst retaining a strong lubricating film.

### Recommended by Aztec Oils as suitable for the following applications

Designed for the lubrication of locomotive bearings. This product may be used for the lubrication of industrial gears and bearings where the use of an EP containing product would result in staining.

### Benefits

- Does not damage paintwork or cause staining on phosphor bronze, brass or copper fittings.
- Excellent wicking ability.
- Prolongs efficiency of under-keep pads by not causing glazing thus extending the service life.
- Will not 'etch' motions.

### Typical Test Data

Appearance		Dark amber/brown
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.90
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	460
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	30
Viscosity Index	ASTM D2207	94

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.