

NDX 40

Product Code: STO031 | **Revision:** 20240820



Non-detergent/dispersant monograde locomotive engine oil.

Available Pack Sizes



Applications

A range of monograde engine oils designed for diesel locomotives where a non-detergent/dispersant lubricant is required for engines with limited or no filtration system. These lubricants are suitable for older engines where modern additive packs could have a detrimental effect on engine components.

Recommended by Aztec Oils as suitable for the following applications

API CA

Benefits

- Superior resistance against rust and oxidation.
- Good anti-wear characteristics.
- Suitable for diesel locomotive engines without filtration systems.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.89
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	140
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	14.3
Pour Point (°C)	ASTM D97	<-10
Total Base Number (mg KOH/g)	ASTM D2896	3.0
Viscosity Index	ASTM D2207	100

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.