


## COOLSPEC REGULAR IAT CL50

**Product Code:** WIN002 | **Revision:** 20250814



Traditional MEG antifreeze & coolant, ready-to-use.

### Available Pack Sizes



### Applications

A premixed traditional inorganic acid technology (IAT) winter antifreeze and summer coolant, manufactured from high-quality monoethylene glycol (MEG) and a two-year inhibitor package. Suitable for use in the cooling systems of cars, motorcycles, vans, commercial and agricultural vehicles where this type of product is required. Provides all year round protection against freezing and overheating whilst preventing scale and corrosion, prolonging the life of your cooling system. This product does not contain nitrites, amines or phosphates (NAP free), making it more environmentally friendly and suitable for a wide range of applications.

### Performance Levels

ASTM D3306  
BS 6580:2010  
SAE J 1034  
UNE 26-361

### Benefits

- Compatible with rubber & plastics used in the cooling system.
- Excellent anti-foaming characteristics.
- Excellent corrosion protection of all materials used in vehicle cooling systems, including aluminium & ferrous metals.
- Meets most international & european standards.
- Superb thermal characteristics that permit effective engine cooling without boiling.
- Suitable for use in petrol & diesel engines.
- -37°C freeze protection - prediluted & ready to use.

### Typical Test Data

Appearance	Blue liquid	
Density @ 20°C	Kg/m <sup>3</sup>	1.07
Equilibrium Reflux Boil Point		169°C
Freezing Point	50% conc. 50% H <sub>2</sub> O	-37°C
pH @ 25°C	50% conc. 50% H <sub>2</sub> O	8.7
Water Content		50%

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and changes must be carried out in accordance with the manufacturers' recommendations.
- Contains bittering agent.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures exceeding 30°C & should be kept out of direct sunlight.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.