

SUPREME SILICATED OAT SI15

Product Code: WIN016 | **Revision:** 20250128



Si-OAT type antifreeze & coolant, ready-to-use.

Available Pack Sizes



Applications

A premium hybrid-organic acid technology engine coolant based on ethylene glycol. This product employs the latest antifreeze technology which combines the benefits of both organic and traditional mineral (silicate) technology. Suitable for use in both petrol and diesel engines and has been introduced to meet the demands of OEMs.

Recommended by Aztec Oils as suitable for the following applications

Audi, VW Group TL-774 G
BS 6580:2010
Cummins CES 14603
Daimler Truck DTFR 29D120
Deutz DQC CC-14
Lieberr Min LH-01-COL3A
MAN 324 Type Si-OAT
Mercedes-Benz 325.6
Scania TB145

Benefits

- Compatible with rubber and plastics used in the cooling system.
- Effective protection for Aluminium components from erosion and cavitation.
- Excellent anti-foaming characteristics.
- Good corrosion protection of all metals and alloys used in the cooling system of modern vehicles.
- Meets most International and European Standards.
- Stabilised silicate additives and organic acid for superior short & long-term corrosion protection (aluminium engines.)
- Superb thermal characteristics that permit effective engine cooling without boiling.
- Suitable for use in petrol and diesel engines.
- -38°C freeze protection - prediluted and ready to use.

Typical Test Data

Appearance	Pink/lilac liquid	
Density @ 15°C (kg/m3)		1.125
Equilibrium Reflux Boil Point		167°C
Foaming Characteristics @ 88°C	Height (ml)	40
Foaming Characteristics @ 88°C	Breaktime (seconds)	1
Freeze Protection	50% conc. 50% H ₂ O	-38°C
Reserve Alkalinity	ml HCl N/10	9.0
pH @ 25°C	50% conc. 50% H ₂ O	8.4
Water Content		50%

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and changes must be carried out in accordance with the manufacturers' recommendations.
- Contains bittering agent.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures exceeding 30°C & should be kept out of direct sunlight.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.