


AGRITEC UTTO SS HD

Product Code: AGR022 | **Revision:** 20251210



Premium heavy-duty, semi-synthetic universal tractor transmission oil, SAE 10W-40.

Available Pack Sizes



Applications

A premium, semi-synthetic universal transmission and hydraulic fluid specifically developed for use in agricultural and plant equipment, including transmissions, hydraulics, rear axles and oil-immersed wet brakes. Formulated using high-quality base oils and advanced additive technology, this high-performance UTTO meets the stringent performance demands of major equipment manufacturers. It offers superior protection, excellent thermal and oxidative stability, and smooth, reliable operation under high-load conditions, ensuring long-lasting durability in the most demanding working environments.

Recommended by Aztec Oils as suitable for the following applications

API GL-4
Allison C4
Case MS 1210
Caterpillar TO-2
Ford M2C86-B/C, M2C134-D
John Deere J20C
Massey Ferguson M1143, M1145
ZF TE-ML 03E, 05F, 06K, 17E, 21F

Benefits

- Allows for rationalisation of products.
- Good resistance against aeration & foaming.
- Formulated to provide strong oxidation resistance, enhanced thermal stability & reliable performance at low operating temperatures.
- Excellent brake squawk & chatter suppression.
- Exceptional anti-wear properties.
- Provides constant frictional performance.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.87
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	95
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	13.5
Pour Point (°C)	ASTM D97	-36
SAE Viscosity		10W-40
Viscosity Index	ASTM D2207	143

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.