


AGRITEC FORESTRY CHAINSAW 220FXT

Product Code: AGR031 | **Revision:** 20251210



Premium, extra-tacky anti-fling cutter bar lubricant for chainsaws.

Available Pack Sizes



Applications

A premium, tenacious and extra-tacky lubricant specially developed for the lubrication of chainsaw cutter bars in heavy-duty forestry equipment. Formulated with advanced surface-active agents, it ensures deep penetration into the chain for maximum wear reduction, superior corrosion protection and exceptional resistance to fling-off during operation. Specifically designed for equipment requiring enhanced levels of tackiness, it delivers consistent performance and long-lasting protection in demanding forestry applications.

Recommended by Aztec Oils as suitable for the following applications

ISO 6743-1 L-AC
Designed for use with heavy-duty forestry equipment that requires additional levels of tackiness. Primarily for the lubrication of cutter bars and chains of pump & pressure-fed chainsaws requiring an ISO 220 or SAE 50 lubricant.

Benefits

- Advanced EP & extremely high levels of tackiness.
- Improves chain life.
- Protects chain links against corrosion.
- Resistant against oil fling.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.89
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	220
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	20
Pour Point (°C)	ASTM D97	-10
Viscosity Index	ASTM D2207	102

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.