

MANUTEC COMPRESSOR M 150

Product Code: COMP003 | **Revision:** 20260202



Mineral based ashless lubricant for reciprocating & rotary vane compressors.

Available Pack Sizes

20L

205L

Applications

Blended from carefully selected high-quality base oils and advanced additive technology, this product is engineered to support extended service intervals of up to 4,000 hours while minimising carbonisation and deposit formation and promoting effective separation from condensates and water. It delivers excellent protection against wear, corrosion, oxidation and foaming, helping to maintain system cleanliness, reliability and long-term performance. Excellent filterability preserves filter efficiency over extended periods, while good low temperature fluidity and enhanced oxidation stability ensure dependable operation across a wide range of conditions, enhancing compressor efficiency and reducing operating costs.

Recommended by Aztec Oils as suitable for the following applications

DIN 51506 VD-L
ISO/TS 6521-2 DAA/DAB/DAH (DAG)
ISO 6743-3 DAA/DAB/DAH (DAG)

Benefits

- Demulsifying to ensure rapid water separation.
- Excellent anti-wear characteristics.
- Good anti-foam & air release properties.
- Outstanding corrosion protection.
- Superior oxidation resistance to provide a long service life.

Typical Test Data

Appearance		Straw/light amber liquid
Copper Corrosion	ASTM D130 A&B	Pass
Density @ 15°C (kg/m ³)	ASTM D4052	0.88
Demulsibility	ASTM D1401	40-40-0
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	150
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	14.9
Oxidation	ASTM D943	4000hrs
Pour Point (°C)	ASTM D97	<-20
Viscosity Index	ASTM D2207	99

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.