

EMPROTEC SDX 20W

Product Code: MON010 | **Revision:** 20260420



Monograde mineral based engine oil.

Available Pack Sizes



Applications

A high-quality monograde engine oil formulated from carefully selected mineral base oils and a balanced additive system designed to deliver dependable engine protection under a wide range of operating conditions. It provides effective resistance against wear, corrosion and oxidation, helping to maintain engine cleanliness and component longevity. Suitable for use in both turbocharged and naturally aspirated petrol and diesel engines where a monograde lubricant is specified by the manufacturer.

Recommended by Aztec Oils as suitable for the following applications

API SG/CF-4
Caterpillar TO-2
MAN 270
Mercedes-Benz 228.1
ZF TE-ML 06A, 07D

Benefits

- Suitable for turbocharged & naturally aspirated petrol & diesel engines.
- Powerful detergent/dispersant additive technology.
- Protection against wear and corrosion.
- SAE 10W, 20W and 30 are suitable for transmission and hydraulic systems in off-highway uses.
- SAE 30, 40 and 50 are suitable for use in petrol and diesel engines where this type of oil is specified.
- SAE 50 where specified is suitable for use in gearboxes.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>210
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	72
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	9.0
Pour Point (°C)	ASTM D97	<-25
Total Base Number (mg KOH/g)	ASTM D2896	9.0
Viscosity Index	ASTM D2207	98

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.