

MOTOTEC FS 2-STROKE

Product Code: MOT037 | **Revision:** 20250303



High-performance fully synthetic two stroke oil.

Available Pack Sizes



Applications

A highly-advanced fully-synthetic two-stroke oil for use in modern, high-speed and high-performance motorcycle engines. Specially developed with our Adaptive Molecular Technology to deliver ultimate performance by enhancing throttle response for faster acceleration, improved lubricity and reduced engine wear whilst promoting clean, efficient combustion and reduced exhaust smoke to deliver the best performance for your motorcycle, whether your next adventure is on or off the road.

Recommended by Aztec Oils as suitable for the following applications

API TC
JASO FC/FD
ISO-L-EGD
Suitable to use with oil injection and pre-mix systems.

Mix with petrol in the ratio recommended by the equipment manufacturer.

Benefits

- Clean burn characteristics reduce carbon build-up, preventing piston ring sticking and reduces smoke emissions.
- Excellent deposit and wear control.
- Exceptional film strength in high-heat, high-rpm engines.
- Power protection formulation provides superior protection against piston seizure, even at high temperatures when tested with very low oiling rates.
- Readily miscible in petrol.

Typical Test Data

Appearance		Clear & bright, red
Density @ 15°C (kg/m ³)	ASTM D4052	0.853
Flash Point (°C)	ASTM D92	110
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	43.7
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	7.9
Pour Point (°C)	ASTM D97	-38
Viscosity Index	ASTM D2207	154

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.