

TOROTEC 0W-20 VL (Export)

Product Code: PCM028 | **Revision:** 20241119



Fully synthetic & low viscosity automotive engine oil.

Available Pack Sizes



Applications

A fully synthetic and low viscosity engine oil formulated for use with modern petrol and diesel engines, particularly those requiring ILSAC GF-5. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle.

Recommended by Aztec Oils as suitable for the following applications

API SN/CF
ILSAC GF-5

May also be suitable to use with Honda, Hyundai, Infiniti, Kia, Lexus, Mazda, Nissan, Suzuki, and Toyota vehicles.

Benefits

- Compatible with engines using the latest Hybrid technology.
- Excellent low temperature performance.
- Improved performance and fuel efficiency.
- Long service intervals.
- Long term anti-wear and oxidation stability.
- Outstanding protection against wear, rust and corrosion.

Typical Test Data

Density @ 15°C (kg/m³)	ASTM D4052	0.844
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm²/s)	ASTM D445	48
Kinematic Viscosity @ 100°C (mm²/s)	ASTM D445	8.8
Pour Point (°C)	ASTM D97	-48
Total Base Number (mg KOH/g)	ASTM D2896	8.0
Viscosity Index	ASTM D2207	165

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.