


## MANUTEC ROCKDRILL M 100

**Product Code:** ROC004 | **Revision:** 20260126



Heavy-duty mineral oil based lubricant for pneumatic rockdrills.

### Available Pack Sizes



### Applications

Rockdrill oils are specially formulated for the lubrication of heavy-duty percussion and rotary pneumatic tools, such as road breakers. Carefully selected base oils provide excellent resistance to waxing, resulting in a low pour point. Advanced additive technology delivers strong adhesiveness, extreme pressure performance, effective rust and corrosion protection and good emulsifiable characteristics. These adhesive and emulsifiable properties help displace water, maintain a continuous lubricating film, improve oil retention on components and extend tool service life.

### Recommended by Aztec Oils as suitable for the following applications

ISO 6743-11 PAB  
Recommended for the lubrication of pneumatic tools, including rock drills, percussion drills, pavement breakers and jackhammers.

### Benefits

- Excellent corrosion resistance.
- Extreme pressure properties providing protection against wear from high-loads.
- Good adhesiveness to metal surfaces in the presence of moisture.
- Outstanding anti-oxidant properties.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.89
Flash Point (°C)	ASTM D92	>230
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	100
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	11.2
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	97

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.